

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Addiese: COMMISSIONER FOR PATENTS P O Box 1450 Alexandra, Virginia 22313-1450 www.wepto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/585,934	01/04/2007	Samuel Boutin	293409US2X PCT	9277	
22850 7590 02/13/2099 OBLON, SPIVAK, MCCLELLAND MAIER & NEUSTADT, P.C. 1940 DUKE STREET			EXAM	EXAMINER	
			LEVIN, NAUM B		
ALEXANDRIA, VA 22314			ART UNIT	PAPER NUMBER	
			2825		
			NOTIFICATION DATE	DELIVERY MODE	
			02/13/2009	ELECTRONIC	

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

patentdocket@oblon.com oblonpat@oblon.com jgardner@oblon.com

Application No. Applicant(s) 10/585,934 BOUTIN, SAMUEL Office Action Summary Examiner Art Unit NAUM B. LEVIN 2825 -- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --Period for Reply A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS. WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION. Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication. If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b). Status 1) Responsive to communication(s) filed on 13 July 2006. 2a) ☐ This action is FINAL. 2b) This action is non-final. 3) Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213. Disposition of Claims 4) Claim(s) 1-9 is/are pending in the application. 4a) Of the above claim(s) _____ is/are withdrawn from consideration. 5) Claim(s) _____ is/are allowed. 6) Claim(s) 1-9 is/are rejected. 7) Claim(s) _____ is/are objected to. 8) Claim(s) _____ are subject to restriction and/or election requirement. Application Papers 9) The specification is objected to by the Examiner. 10)⊠ The drawing(s) filed on 04 January 2007 is/are: a)⊠ accepted or b) objected to by the Examiner. Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a). Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d). 11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152. Priority under 35 U.S.C. § 119 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No. Copies of the certified copies of the priority documents have been received in this National Stage

Attachment(s)

1) ☑ Notice of References Cited (PTO-892)

2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3) ☑ Informition-Deckouse Cohemona(s) (PTO/65/CC)

Paper No(s)/Mail Date 10/12/05

6) ☐ Other: _____

application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Art Unit: 2825

DETAILED ACTION

This office action is in response to application 10/585,934 filed on 07/13/2006.
 Claims 1-9 are pending in the application.

Specification

- This application does not contain an abstract of the disclosure as required by 37 CFR 1.72(b). An abstract on a separate sheet is required.
- The title of the invention is not descriptive. A new title is required that is clearly indicative of the invention to which the claims are directed.

The following title is suggested: method for design and verification of safety critical systems.

Claim Rejections - 35 USC § 101

35 U.S.C. 101 reads as follows:

Whoever invents or discovers any new and useful process, machine, manufacture, or composition of matter, or any new and useful improvement thereof, may obtain a patent therefor, subject to the conditions and requirements of this title.

4. Claim 1 is rejected under 35 U.S.C. 101 because the claimed invention is directed to non-statutory subject matter. A method that recites purely mental steps is descriptive material and is nor statutory if not claimed as method (1) tied to another statutory class (such as a particular apparatus) or (2) transform underlying subject matter (such as an article or materials) to a different state or thing (See in re *Bilski*, 545 F.3d 943, 88 USPQ2d 1385 (Fed. Cir. 2008)).

Page 3

Application/Control Number: 10/585,934

Art Unit: 2825

5. Claim 1 is also rejected under 35 U.S.C. 112, first paragraph. Specifically, since the claimed invention is not supported by either a claims or Specification asserted utility or a well established utility for the reasons set forth above, one skilled in the art clearly would not know how to use the claimed invention.

- 6. Claim 8 is rejected under 35 U.S.C. 101 because the claimed invention is directed to non-statutory subject matter. A computer program product comprising a computer readable medium is descriptive material and is nor statutory (See MPEP 2106.01) if not claimed as a computer-readable storage device for storing computer-executable software/instructions/program because the computer program product comprising a computer readable medium is non-statutory subject matter per se (for example, a carrier wave).
- 7. Claim 8 is also rejected under 35 U.S.C. 112, first paragraph. Specifically, since the claimed invention is not supported by either a claims or specification asserted utility or a well established utility for the reasons set forth above, one skilled in the art clearly would not know how to use the claimed invention.

Claim Rejections - 35 USC § 112

The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

Claim 9 is objected to under 37 CFR 1.75(c) as being in improper form
 because a multiple dependent claim cannot depend from any other multiple dependent

claim. See MPEP § 608.01(n). Accordingly, the claim has not been further treated on the merits

Also a tool as in method/process claims 1 to 7 programmed/made by a program of claim 8 is improper

 Regarding claims 1, 2, 7 and 8 the phrases "for example" "e.g." render the claims indefinite because it is unclear whether the limitation(s) following the phrase are part of the claimed invention. See MPEP § 2173.05(d).

Claim Objections

10. Claims1-9 are objected to because of the following informalities:

The numbering of claims is not in accordance with 37 CFR 1.126 which requires the original numbering of the claims to be preserved throughout the prosecution. When claims are canceled, the remaining claims must not be renumbered. When new claims are presented, they must be numbered consecutively beginning with the number next following the highest numbered claims previously presented (whether entered or not).

Misnumbered claim1-9 must be renumbered.

11. Claim 3 is objected to because of the following informalities:

Replace "state chars" with -- state charts --.

- 12. In claims 1 and 8 Applicant must clarify what is "where possible" (what will be "where not possible"?).
 - 13. Claim 9 is objected to because of the following informalities:

Replace "to implements" with -- to implement --.

Page 5

Application/Control Number: 10/585,934

Art Unit: 2825

Appropriate correction is required.

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- Claims 1-6, 8-9 are rejected under 35 U.S.C. 102(b) as being unpatentable
 Torres-Pomales (Software Fault Tolerance: A Tutorial; Technical Report: NASA-2000-tm210616; Year of Publication: 2000; pages 1-55).
 - 15. As to claims 1 and 8 Torres-Pomales discloses:
- Claim 1 A method of producing a system architecture comprising a plurality of electrical devices connected to each other, said system preferably comprising a fault tolerant system (page 2, paragraph 5; page 34, last paragraph; page 35, paragraph 1; Fig.1), the method including:
- a) identifying a set of undesirable events and ascribing to each of said undesirable events an indicator of their severity (A system safety design begins by performing modeling and analysis to identify and categorize potential hazards. This is followed by the use of analysis techniques to assign a level of severity of occurrence to the identified hazards page 8, paragraph 4);
- b) associating where possible each said undesirable event with one or
 more actuators of said system architecture (As best understood, upon detection of a

Page 6

Application/Control Number: 10/585,934

Art Unit: 2825

computer or actuator failure/associating where possible each said undesirable event, control is passed to another computer based on a predetermined hand over sequence – page 37, last paragraph);

- c) developing a functional specification of an initial architecture proposed for implementation of said system architecture, said functional specification of said initial architecture (The initial design of this flight control computer was a four by three configuration including hardware and software/ functional specification dissimilarity in all the channels. Software diversity was to be achieved through the use of different programming languages targeting different lane processors. The final and current implementation uses only one programming language with the executable code being generated by three different compilers still targeting dissimilar lane processors. The lane processors are dissimilar because they are the single most complex hardware devices, and thus there is a perceived risk of design faults associated with their use page 36, last paragraph) including dataflow for and between components thereof, said components comprising for example sensors or actuators (page 4, paragraph 2; page 35, Fig.19);
- d) refining on said functional specification the fault tolerance requirements associated with the severity of each said undesirable event and issuing refined fault tolerance requirements of said functional specification(Figure 2 presents the Prototyping Process Model. This process model is appropriate for projects where the requirements are incompletely specified or when the developers are unsure whether a proposed design solution is adequate. The process begins with a requirements capture

Art Unit: 2825

activity, followed by a quick design and build of a prototype or mock-up of the product.

After analyzing the prototype, further refinements to the requirements are generated and the process begins again. This cycle activity not only helps develop the requirements, but it also helps the developers better understand the problem - page 3, paragraph 2);

- e) producing replicates in said functional specification together with attached indicators of independence of said replicates, said indicators reflecting said refined fault tolerance requirements (Multi-version fault tolerance is based on the use of two or more versions (or "variants") of a piece of software, executed either in sequence or in parallel. The versions are used as alternatives (with a separate means of error detection), in pairs (to implement detection by replication checks) or in larger groups (to enable masking through voting). The rationale for the use of multiple versions is the expectation that components built differently (i.e., different designers, different algorithms, different design tools, etc) should fail differently. Therefore, if one version fails on a particular input, at least one of the alternate versions should be able to provide an appropriate output page 10, paragraphs 2-6; page 11; page 12, paragraph 1; page 17, paragraphs 3-4; page 18; pages 19-21);
- f) defining a hardware structure for said system architecture, e.g. a series of electronic control units connected to each other by networks (Fig. 19);
- g) mapping of said functional specification onto said hardware structure (The integration process is the phase of development when the <u>source code is</u> linked

Art Unit: 2825

and <u>transformed</u> into the executable object code to be <u>loaded on the target computer</u> hardware - page 4, paragraph 4); and

h) verifying automatically that said indicators of independence are preserved during mapping (The supporting processes are three: verification, configuration management, and quality assurance. The purpose of the verification process is to search and report errors in the software requirements, design, source code, and integration. Verification is composed of three types of activities: reviews, analysis and testing – page 4, last paragraph, page 5);

Claim 8 A computer program product comprising a computer readable medium having thereon computer program code means, when said program is loaded, to make the computer execute procedure to design and verify system architecture (page 27, paragraphs 2-3), said procedure comprising:

- a) identifying a set of undesirable events and ascribing to each of said undesirable events an indicator of their severity (A system safety design begins by performing modeling and analysis to identify and categorize potential hazards. This is followed by the use of analysis techniques to assign a level of severity of occurrence to the identified hazards page 8, paragraph 4);
- b) associating where possible each said undesirable event with one or more actuators of said system architecture (As best understood, <u>upon detection of</u> a computer <u>or actuator failure/associating where possible each said undesirable event</u>, control is passed to another computer based on a predetermined hand over sequence page 37, last paragraph):

Art Unit: 2825

c) developing a functional specification of an initial architecture proposed for implementation of said system architecture, said functional specification of said initial architecture (The initial design of this flight control computer was a four by three configuration including hardware and software/ functional specification dissimilarity in all the channels. Software diversity was to be achieved through the use of different programming languages targeting different lane processors. The final and current implementation uses only one programming language with the executable code being generated by three different compilers still targeting dissimilar lane processors. The lane processors are dissimilar because they are the single most complex hardware devices, and thus there is a perceived risk of design faults associated with their use – page 36, last paragraph) including dataflow for and between components thereof, said components comprising for example sensors or actuators (page 4, paragraph 2; page 35, Fig.19);

d) refining on said functional specification the fault tolerance requirements associated with the severity of each said undesirable event and issuing refined fault tolerance requirements of said functional specification(Figure 2 presents the Prototyping Process Model. This process model is appropriate for projects where the requirements are incompletely specified or when the developers are unsure whether a proposed design solution is adequate. The process begins with a requirements capture activity, followed by a quick design and build of a prototype or mock-up of the product. After analyzing the prototype, further refinements to the requirements are generated and the process begins again. This cycle activity not only helps develop the

Art Unit: 2825

requirements, but it also helps the developers better understand the problem - page 3, paragraph 2);

- e) producing replicates in said functional specification together with attached indicators of independence of said replicates, said indicators reflecting said refined fault tolerance requirements (Multi-version fault tolerance is based on the use of two or more versions (or "variants") of a piece of software, executed either in sequence or in parallel. The versions are used as alternatives (with a separate means of error detection), in pairs (to implement detection by replication checks) or in larger groups (to enable masking through voting). The rationale for the use of multiple versions is the expectation that components built differently (i.e., different designers, different algorithms, different design tools, etc) should fail differently. Therefore, if one version fails on a particular input, at least one of the alternate versions should be able to provide an appropriate output page 10, paragraphs 2-6; page 11; page 12, paragraph 1; page 17, paragraphs 3-4; page 18; pages 19-21);
- f) defining a hardware structure for said system architecture, e.g. a series of electronic control units connected to each other by networks (Fig. 19);
- g) mapping of said functional specification onto said hardware structure (The integration process is the phase of development when the <u>source code is</u> linked and <u>transformed</u> into the executable object code to be <u>loaded on the target computer hardware</u> page 4, paragraph 4); and
- h) verifying automatically that said indicators of independence are preserved during mapping (The supporting processes are three: verification,

Art Unit: 2825

configuration management, and quality assurance. The purpose of the verification process is to search and report errors in the software requirements, design, source code, and integration. Verification is composed of three types of activities: reviews, analysis and testing – page 4, last paragraph; page 5).

16. As to claims 2-6 and 9 Torres-Pomales recites:

<u>Claim 2</u> A method for defining a series of modes of operation, e.g. nominal and limp-home/degraded modes (page 17, last paragraph);

<u>Claim 3</u> A method that includes specifying said series of modes in the form of one or more state charts (page 12, last paragraph; page 13; page 14, paragraph 1);

Claim 4 A method including mapping geometrically hardware components and/or wiring and then verifying automatically that said indicators of independence are preserved by said geometrical mapping (page 4, last paragraph; page 5):

<u>Claim 5</u> A method including specifying severity in the form of probability of failure per unit of time (page 7, paragraphs 2-4; page 5);

Claim 6 A method according to any preceding claim including outputting a set of data for manufacturing said system architecture (page 26, paragraph 3; page 29, paragraph 1);

Claim 9 A design tool adapted for the design and verification of a system architecture have been programmed using the computer program product according to claim 8 (page 3, paragraph 2; page 4, paragraph 2; page 4, paragraph 2; page 4, paragraph 3; page 4, paragraph 4; page 10, paragraphs 2-6; page 11;

Art Unit: 2825

page 12, paragraph 1; page 17, paragraphs 3-4; page 18; pages 19-21; page 27, paragraphs 2-3; page 35; page 36, last paragraph; page 37, last paragraph; Fig.19).

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 10 of this like it is difference between the subject matter so, but to be patented and the prior are such that the subject matter so, which we have a subject matter so when the way to the subject matter so, and the subject matter so, and the subject matter some shade to a person having ordinary skill in the art to which said subject matter operations. Patentiability shall not be necessitived by the manner in which it evention was made to which said subject matter operations. Patentiability shall not be necessitived by the manner in which it evention was made to which said subject matter operations.

 Claim 7 is rejected under 35 U.S.C. 103(a) as being unpatentable by Torres-Pomales in view of Ivarez-Troncoso et al. (U.S. Patent 7,076,350).

With respect to claim 7 Torres-Pomales teaches the features above but lacks a method, wherein a system architecture comprises an architecture for a safety control circuitry of a brake system in a vehicle.

18. As to claim 7 Ivarez-Troncoso recites:

Claim 7 A method, wherein said architecture comprises an architecture for a vehicle, such as safety control circuitry for a brake system (electrical energy, power, and load management (EM) system controls power generation, storage, and consumption according to different operational states of a vehicle. An EM system typically has the capability of disengaging lower priority loads during specific conditions in order to maintain sufficient power to higher priority (e.g., safety-related) loads).

Art Unit: 2825

Electrical system parameters that are monitored and controlled include break system of the vehicle - col.2. lines 34-67; col.3. lines 1-19).

It would have been obvious to a person of ordinary skills in the art at the time the invention was made to improve Torres-Pomales' invention by implementing the method, wherein a system architecture comprises an architecture for a safety control circuitry of a brake system in a vehicle by providing an energy management control system for managing events in an electrical system based on forecasted states, thereby avoiding degraded electrical system performance without excessive processing requirements (col.1, lines 49-64).

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to NAUM B. LEVIN whose telephone number is (571)272-1898. The examiner can normally be reached on M-F (8:00-4:30).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Jack Chiang can be reached on 571-272-7483. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2825

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Naum Levin/ Examiner Art Unit 2825